

PRODUCT NO. 359025



ZenXtreme™ Ceramic Spray Coating

A ready-to-use (RTU) liquid SiO₂-based ceramic detailing spray engineered to form a durable, hydrophobic silica layer that actively repels water, dirt, and light contaminants. The advanced silica bonding enhances painted, coated, and glass surfaces by reinforcing existing protection or providing standalone coverage, while mitigating oxidation, UV-induced fading, and environmental wear. It imparts deep gloss, wet-look shine, and an ultra-slick finish for easier maintenance, superior surface clarity, and enhanced water-shedding performance. Designed for professionals and enthusiasts, it delivers long-lasting surface protection with minimal application time, supporting superior detailing results and efficient upkeep.

FEATURES & BENEFITS

- Deep, reflective gloss and wet-look shine
- Hydrophobic surface for rapid water sheeting and beading
- Protects against UV exposure, oxidation, and environmental contaminants for up to 6 months
- Improves surface slickness for easier cleaning and maintenance
- Compatible with painted, coated, glass, plastics and trim surfaces
- Not suitable for use on rubber tires or interior surfaces

PERFORMANCE RECOMMENDATIONS

- For best results, allow 2-4 hours' time post-application for optimal bonding to surfaces.
- Avoid washing the vehicle with harsh chemicals or using abrasive compounds on surfaces.
- Reapply as needed to maintain gloss and hydrophobic performance, typically every 3–6 months depending on environmental conditions.

DIRECTIONS FOR USE

SURFACE PREPARATION

1. Wash and dry the vehicle thoroughly to remove dirt, road grime, and contaminants.
2. For optimal results, decontaminate painted or coated surfaces using clay or a paint-safe iron particle remover.
3. Ensure surfaces are cool to the touch and out of direct sunlight before application.
4. If applying in direct sunlight, always spray on microfiber towel to apply, not directly on the surface.

APPLICATION

5. Shake the bottle well before use.
6. Spray the product evenly onto the surface, working panel by panel.
7. Use a clean microfiber towel to spread and level the product across the surface.

ALTERNATE APPLICATION

5. Shake the bottle well before use.
6. Apply a minimal amount of product to a clean, soft microfiber applicator or towel.
7. Apply the product evenly onto the surface, working panel by panel.

BUFFING AND FINISHING

8. Allow the product to dwell for 1–2 minutes after application.
9. If a light haze forms (depending on ambient temperature and surface), gently buff with a clean, dry microfiber towel to achieve uniform gloss and clarity.

PRODUCT NO. 359025

ZenXtreme™ Ceramic Wash

PHYSICAL CHARACTERISTICS	
PHYSICAL FORM	Liquid
VISCOSITY	Water Thin
COLOR	White
FRAGRANCE	Mild
GLOSS	High
SHELF LIFE	1 Year
REGULATORY	
SPECIFIC GRAVITY	1.0 g/mL
FLASH POINT	>200°F
PH	7
CA COMPLIANT	Yes
PROP 65	Yes
SHIPPING NAME	N/A