

# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: 493705  
Product Name: ZenaCore Clean Plus  
Revision Date: Aug 10, 2026  
Version: 2.0  
Manufacturer's Name: Zenex International  
Address: 1 Zenex Circle Cleveland, OH, US, 44146  
Emergency Phone: 1-800-535-5053  
Information Phone Number: (440)-232-4155  
Fax:  
Product/Recommended Uses: A/C Evaporator Cleaner

Date Printed: Aug 10, 2026  
Supersedes Date: Mar 19, 2025

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Aerosols - Category 2  
Eye Irritation - Category 2A

### Pictograms



### Signal Word

Warning

### Hazardous Statements - Physical

H223 - Flammable aerosol.  
H229 - Pressurized container; may burst if heated.

### Hazardous Statements - Health

H319 - Causes serious eye irritation.

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read carefully and follow all instructions.

### Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye and face protection.

### Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

### Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

### Precautionary Statements - Disposal

No precautionary statements.

## SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

| CAS        | Chemical Name                                 | % By Weight |
|------------|-----------------------------------------------|-------------|
| 68476-86-8 | Petroleum gases, liquefied, sweetened         | 1% - 10%    |
| 68920-42-3 | Bacteria, complex with amylase and proteinase | 1% - 3%     |
| 137-16-6   | Sodium N-lauroylsarcosinate                   | 1% - 3%     |
| 9036-19-5  | Polyethylene glycol octylphenyl ether         | 0% - 1%     |
| 6834-92-0  | Silicic acid, disodium salt                   | 0% - 1%     |
| 7632-00-0  | Sodium nitrite                                | 0% - 1%     |
| Mixture    | Fragrance                                     | 0% - 1%     |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband.

### Eye Contact

Immediately flush eyes with plenty of water. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most Important Symptoms/Effects, Acute and Delayed

No data available.

### Indication of Immediate Medical Attention and Special Treatment Needed

No data available.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

### Unsuitable Extinguishing Media

Do not use water jet.

### Specific Hazards in Case of Fire

Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous decomposition products may form and include the following materials: Carbon oxides

### Fire-Fighting Procedures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### Special Protective Actions

Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**Small spill:** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill:** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Stop spill/release if it can be done safely.

## SECTION 7) HANDLING AND STORAGE

### General

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

### Storage Room Requirements

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### Respiratory Protection

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

### Appropriate Engineering Controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

| Chemical Name | OSHA TWA<br>(mg/m3) | OSHA TWA<br>(ppm) | OSHA STEL<br>(mg/m3) | OSHA<br>Carcinogen | OSHA Skin<br>designation | OSHA Tables (Z1,<br>Z2, Z3) | ACGIH TWA<br>(mg/m3) | ACGIH TWA<br>(ppm) |
|---------------|---------------------|-------------------|----------------------|--------------------|--------------------------|-----------------------------|----------------------|--------------------|
| BUTANE        |                     |                   |                      |                    |                          |                             |                      |                    |
| PROPANE       | 1800                | 1000              |                      |                    |                          | 1                           |                      |                    |

| Chemical Name | NIOSH STEL<br>(ppm) | ACGIH STEL<br>(mg/m3) | ACGIH STEL<br>(ppm)                                   | ACGIH<br>Carcinogen | ACGIH TLV<br>Basis | ACGIH<br>Notations | NIOSH TWA<br>(mg/m3) | NIOSH TWA<br>(ppm) |
|---------------|---------------------|-----------------------|-------------------------------------------------------|---------------------|--------------------|--------------------|----------------------|--------------------|
| BUTANE        |                     |                       | 1000 (EX)                                             |                     | CNS impair         |                    | 1900                 | 800                |
| PROPANE       |                     |                       | Simple<br>asphyxiant (D),<br>explosion<br>hazard (EX) |                     | Asphyxia           |                    | 1800                 | 1000               |

| Chemical Name | NIOSH STEL<br>(mg/m3) | OSHA STEL<br>(ppm) | NIOSH<br>Carcinogen |
|---------------|-----------------------|--------------------|---------------------|
| BUTANE        |                       |                    |                     |
| PROPANE       |                       |                    |                     |

(C) - Ceiling limit, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

|                       |                    |
|-----------------------|--------------------|
| Density               | 8.3 lb/gal         |
| Density VOC           | 0.37 lb/gal        |
| % VOC                 | 4.41%              |
| Appearance            | Colorless Liquid   |
| Odor Threshold        | N.A.               |
| Odor Description      | Fragrant           |
| pH                    | 7-8                |
| Water Solubility      | N.A.               |
| Flammability          | N.A.               |
| Vapor Pressure        | 95 x 104 (Propane) |
| Flash Point           | -104°C (Propane))  |
| Viscosity, Kinematic  | N.A.               |
| Lower Explosion Level | 2.1%               |
| Upper Explosion Level | 9.5%               |
| Vapor Density         | N.A.               |
| Melting Point         | N.A.               |
| Freezing Point        | N.A.               |

|                    |      |
|--------------------|------|
| Low Boiling Point  | N.A. |
| High Boiling Point | N.A. |
| Decomposition Pt   | N.A. |
| Auto Ignition Temp | N.A. |
| Evaporation Rate   | N.A. |

## SECTION 10) STABILITY AND REACTIVITY

### Stability

The product is stable under normal storage conditions.

### Conditions to Avoid

Keep away from heat, sparks, extreme temperature, flame, other sources of ignition and incompatible materials.

### Incompatible Materials

Strong oxidizing agents

### Hazardous Reactions/Polymerization

Under normal conditions of storage and use, hazardous reactions will not occur.

### Hazardous Decomposition Products

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Skin Corrosion/Irritation

No data available.

### Likely Route of Exposure

Inhalation, eye contact, skin absorption.

### Serious Eye Damage/Irritation

Causes serious eye irritation

### Carcinogenicity

No data available.

### Germ Cell Mutagenicity

No data available.

### Reproductive Toxicity

No data available.

### Respiratory/Skin Sensitization

No data available

### Specific Target Organ Toxicity - Single Exposure

No data available.

### Specific Target Organ Toxicity - Repeated Exposure

No data available

### Aspiration Hazard

No data available.

### Acute Toxicity

No data available.

## SECTION 12) ECOLOGICAL INFORMATION

### Toxicity

No data available.

## Persistence and Degradability

No data available.

## Bio-Accumulative Potential

No data available.

## Mobility in Soil

No data available.

## Other Adverse Effects

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

## SECTION 14) TRANSPORT INFORMATION

|                           | U.S. DOT Information | IMDG Information  | IATA Information    |
|---------------------------|----------------------|-------------------|---------------------|
| UN number:                | UN1950               | UN1950            | UN1950              |
| Proper shipping name:     | Aerosols             | Aerosols          | Aerosols, flammable |
| Hazard class:             | 2.1                  | 2.1               | 2.1                 |
| Packaging group:          | N.A.                 | N.A.              | N.A.                |
| Hazardous substance (RQ): | No Data Available    |                   |                     |
| Marine Pollutant:         | No Data Available    | No Data Available |                     |
| Note / Special Provision: | (LTD QTY)            | (LTD QTY)         | (LTD QTY)           |
| Toxic-Inhalation Hazard:  | No Data Available    |                   |                     |

## SECTION 15) REGULATORY INFORMATION

| CAS        | Chemical Name                                 | % By Weight | Regulation List                    |
|------------|-----------------------------------------------|-------------|------------------------------------|
| 68476-86-8 | Petroleum gases, liquefied, sweetened         | 1% - 10%    | SARA312, VOC, TSCA, ACGIH, OSHA    |
| 68920-42-3 | Bacteria, complex with amylase and proteinase | 1% - 3%     | SARA312, TSCA                      |
| 137-16-6   | Sodium N-lauroylsarcosinate                   | 1% - 3%     | SARA312, TSCA, ACGIH               |
| 9036-19-5  | Polyethylene glycol octylphenyl ether         | 0% - 1%     | CERCLA, SARA312, TSCA, ACGIH, OSHA |
| 6834-92-0  | Silicic acid, disodium salt                   | 0% - 1%     | CERCLA, SARA312, TSCA, ACGIH, OSHA |
| 7632-00-0  | Sodium nitrite                                | 0% - 1%     | CERCLA, SARA312, TSCA, ACGIH, OSHA |
| Mixture    | Fragrance                                     | 0% - 1%     |                                    |

## SECTION 16) OTHER INFORMATION


### Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

#### HMIS

|                     |   |
|---------------------|---|
| Health              | 1 |
| FLAMMABILITY        | 4 |
| Physical Hazard     | 0 |
| Personal Protection | B |

#### NFPA



(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.