

PRODUCT NO. 494535



ZenaGasket Red

LOW VOLATILITY HIGH TEMP RTV GASKET MAKER

As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics & high chemical resistance. Will not sag or shrink and is impervious to temperature extremes.

FEATURES & BENEFITS

- Temperature range of (-76°F to +450°F) (continuous); (+500°F) (short periods)
- Permanently flexible
- Safe to use on oxygen sensors

APPLICATIONS & USES

Will adhere to clean metal, glass, most types of wood, silicone resin, vulcanized rubber, ceramic, natural and synthetic fiber as well as painted and plastic surfaces. Forms in-place gaskets for oil and transmission pans, oil and water pumps, valve and timing chain covers, electric motors and electric control boxes, gear boxes, compressors, and machine covers.

DIRECTIONS FOR USE

1. Surface must be clean, dry, and free of oil, tar, dirt, and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surface, encircling all bolt holes.
3. For adhesion to both parts, assemble immediately. One part adhesion, allow 10 to 15 minutes for bead to skin.
4. Assemble parts, but do not squeeze gasket out by over tightening bolts.
5. Starts to cure immediately, fully cures in 24 hours, and reaches optimum strength in 7 days.

SIZE / AVAILABILITY

CAN SIZE: 8 oz
NET WEIGHT: 8 oz
QUANTITY: 6 per case
SHIPPING WEIGHT: 5 lbs

PHYSICAL CHARACTERISTICS	
COLOR	Red
FRAGRANCE	Acetic Acid
SPRAY PATTERN	Paste
SHELF LIFE	1 Year +
REGULATORY	
OZONE DEPLETING COMPOUNDS	None
RECYCLABLE PACKAGING	Yes
VOC COMPLIANT CARB/OTC	Yes
SHIPPING NAME	Aerosols (LTD QTY)
24 HOUR MEDICAL EMERGENCY	1-866-836-8855