


PRODUCT NO. 494645



Anti-Seize Copper

PREMIUM ANTI-SEIZE LUBRICANT

A premium grade copper fortified anti-seize lubricant formula that adheres, lubricates, protects, and seals. Excellent adhesion and water-repelling capabilities help to reduce torque and prevent galling, seizing, and galvanizing of metals. Great for applications where extreme pressure and long-term protection is required and tough outdoor environmental conditions exist. Product will not melt, gum-up, or harden and is compatible with other lubricants.

FEATURES & BENEFITS

- Lubricates, protects, and seals
- Excellent adhesion and clinging properties
- Use on nuts, bolts, studs, discs, and drum brakes
- Ultimate protection in high temperature environments up to 2000°Ft

APPLICATIONS & USES

Acts as a lubricant on bearings and slides. Excellent for use on fittings, nuts, screws, pipes, exhaust manifold bolts, winches, conveyors, compressors, flanges, bearings, motors, gears, & more.

DIRECTIONS FOR USE

1. Shake the can vigorously for one minute after the mixing ball begins to rattle.
2. Make sure surface is cleaned of all dirt, grease, and grime.
3. Spray a liberal amount from a distance of 8-10 inches.
4. Invert can after use and spray short bursts to clear the valve.

SIZE / AVAILABILITY

CAN SIZE: 16 oz
NET WEIGHT: 14 oz
QUANTITY: 12 per case
SHIPPING WEIGHT: 15 lbs

PHYSICAL CHARACTERISTICS	
COLOR	Dark Brown
FRAGRANCE	Solvent
SPRAY PATTERN	Stream
SHELF LIFE	1 Year +
REGULATORY	
OZONE DEPLETING COMPOUNDS	None
RECYCLABLE PACKAGING	Yes
VOC COMPLIANT CARB/OTC	Yes
SHIPPING NAME	Aerosols (LTD QTY)
24 HOUR MEDICAL EMERGENCY	1-866-836-8855