


PRODUCT NO. 496205



ZenaLube Dry PTFE

DRY PTFE LUBRICANT & RELEASE AGENT

High grade multiple use lubricant and release agent with excellent microscopic film-forming properties. Resistant to most elements and formulated to reduce friction at medium to low resistance, contains no silicones or petroleum oil, and is ideally suited for use on metal, plastic, and wood.

FEATURES & BENEFITS

- Repels dirt & dust
- Non-oil & non-staining
- Temperature range works from 0°F to 500°F

APPLICATIONS & USES

For use on metal, plastic and wood. Lubricates locks, hinges, equipment linkages, pulleys, bearings, slide mechanisms, gear drives, chain drives, windows, etc. Also recommended as a mold release agent for injection molding applications.

DIRECTIONS FOR USE

1. Shake vigorously for one minute after mixing ball begins to rattle.
2. Clean surface to be treated.
3. Hold from 6 inches and spray a fine thin film on surface. Reapply as needed.

SIZE / AVAILABILITY

CAN SIZE: 16 oz

NET WEIGHT: 11 oz

QUANTITY: 12 per case

SHIPPING WEIGHT: 12 lbs

PHYSICAL CHARACTERISTICS

COLOR	Clear
FRAGRANCE	Solvent
SPRAY PATTERN	Fine Mist
SHELF LIFE	1 Year +
REGULATORY	
OZONE DEPLETING COMPOUNDS	No
RECYCLABLE PACKAGING	Yes
VOC COMPLIANT CARB/OTC	Yes
SHIPPING NAME	Aerosols (LTD QTY)
24 HOUR MEDICAL EMERGENCY	1-866-836-8855