

PRODUCT NO. 496960



ZenaLube Dry Moly

HIGH TEMPERATURE LUBRICANT

Formulated with molybdenum disulfide for superior anti-friction and anti-seize performance, this lubricant adheres to most surfaces while repelling dust and dirt. Free of methylene chloride, it improves operating efficiency and reduces maintenance costs by resisting corrosion from water, alkalis, and acids.

FEATURES & BENEFITS

- Fast drying
- Non-corrosive, oil-free formula
- Wide range of operating temperatures from -28°F to 600°F
- Does not contain methylene chloride

APPLICATIONS & USES

Designed to use on areas servicing high temperatures (-28°F/- 33°C - 600°F/315°C) and high-pressure conditions.

DIRECTIONS FOR USE

1. Shake vigorously for one minute after mixing ball begins to rattle. Clean surface thoroughly.
2. Hold can 6 to 8 inches from surface and apply evenly.
3. Allow 1 to 5 minutes for adequate drying.
4. Shake vigorously and often.
5. Before storage turn the can upside down and spray until clear.

SIZE / AVAILABILITY

CAN SIZE: 16 oz

NET WEIGHT: 11 oz

QUANTITY: 12 per case

SHIPPING WEIGHT: 13 lbs

PHYSICAL CHARACTERISTICS

COLOR	Black
FRAGRANCE	Solvent
SPRAY PATTERN	Strong Mist
SHELF LIFE	1 Year +
REGULATORY	
OZONE DEPLETING COMPOUNDS	None
RECYCLABLE PACKAGING	Yes
VOC COMPLIANT CARB/OTC	No
SHIPPING NAME	Aerosols (LTD QTY)
24 HOUR MEDICAL EMERGENCY	1-866-836-8855