

PRODUCT NO. 499755



ZenaCutt

CUTTING & TAPPING COMPOUND

A foaming oil that clings to all cutting tools, preventing waste and over spraying. Combines synthetic and natural lubricants for maximum high-pressure lubrication which will increase the cutting rate without overheating. Prevents chip welding and eliminates dangerous and costly tool breakage. Blended for high load tolerance and to leave a temporary rust inhibitive coating.

FEATURES & BENEFITS

- No-Overheating
- Prevents Waste
- Eliminates dangerous and costly tool breakage

APPLICATIONS & USES

Use on all cutting, punching, sawing, tapping, grinding, boring and machining tools to increase the cutting rate without overheating.

DIRECTIONS FOR USE

1. Shake can well before using.
2. Spray moderate amount of foam on cutting tool.
3. Re-spray often, to keep tools cool and well lubricated.

SIZE / AVAILABILITY

CAN SIZE: 16 oz

NET WEIGHT: 14 oz

QUANTITY: 12 per case

SHIPPING WEIGHT: 15 lbs

PHYSICAL CHARACTERISTICS

COLOR	Amber
FRAGRANCE	Pungent
SPRAY PATTERN	Streaming Foam
SHELF LIFE	1 Year
REGULATORY	
OZONE DEPLETING COMPOUNDS	None
RECYCLABLE PACKAGING	Yes
VOC COMPLIANT CARB/OTC	Yes
SHIPPING NAME	Aerosols (LTD QTY)
24 HOUR MEDICAL EMERGENCY	1-866-836-8855